

Performance

Tipping load (ISO 14397-1)	1823 kg
Rated operating capacity (ISO 14397-1)	911 kg
Pump capacity	64.70 L/min
Pump capacity (with high flow option)	101.10 L/min
System relief at quick couplers	23.8-24.5 MPa
Max. travel speed (high range - option)	17.3 km/h
Max. travel speed (low range)	11.8 km/h

Engine

Make / Model	Bobcat 2.4L, 97/68 EC
Compliance	Stage V
Fuel	Diesel
Cooling	Liquid
Power at 2600 RPM (ISO 14396)	41.0 kW
Torque at 1800 RPM (ISO 14396)	204.0 Nm
Number of cylinders	4
Displacement	2392 cm ³
Fuel tank	93.70 L

Weights

Operating weight	2952 kg
Shipping weight	2581 kg

Controls

Vehicle steering	Hand Levers or optional Selectable Joystick Controls (SJC)
Loader hydraulics tilt and lift	Foot Pedals or optional Selectable Joystick Controls (SJC)
Front auxiliary (standard)	Proportional switch on Hand Levers or optional Selectable Joystick Controls (SJC)

Drive System

Transmission	Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors
--------------	---

Standard Features

Bobcat Interlock Control System (BICS)	Spark Arrester
Parking brake	Bob-Tach™ frame
Deluxe operator cab* Includes interior cab foam, side, top and rear windows, Deluxe wire harness, dome light and electrical power port ¹	Cushioned lift and tilt cylinders
Noise reduction kit	Lift arm support
Operating lights, front and rear	Engine/hydraulics system shutdown
Deluxe instrument panel	Automatically activated glow plugs
Keyless start with password capability	Electrically activated proportional front auxiliary hydraulics
Suspension seat	Auxiliary hydraulics: variable flow/maximum flow
Seat belt	Machine IQ (telematic)
Seat bar	Manual
Hydraulic bucket positioning (including ON/OFF switch)	CE certification
10 x 16.5, 10-ply, Heavy duty tyres	Warranty: 24 months or 2000 hours (whichever occurs first)

1. Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I


Options

Deluxe pressurized cab with heating	2 Speed
Deluxe pressurized cab with HVAC	Power Bob-Tach™
Selectable Joystick Controls (SJC - R/C Ready)	Back-up alarm
Cloth Suspension Seat	Radio
10 x 16.5, 10-ply, Heavy duty tyres, offset rims	Beacon
10 x 16.5, 10-ply, Versatile duty tyres	Work Lights LED
10 x 16.5, 10-ply, Severe duty tyres	Road Option
31 x 10 - 20, Industrial duty tyres	Automatic Ride Control
High-flow auxiliary hydraulics	Automatic Reversing Fan
7-pin attachment control	Custom paint color (min order of 5 units)

Environmental

Operator LpA(98/37 & 474-1)	86 dB(A)
Noise level LWA(EU Directive 2000/14/EC)	98 dB(A)
Whole body vibration (ISO 2631-1) High speed	0.86 ms ⁻²
Whole body vibration uncertainty	0.43 ms ⁻²
Hand-arm vibration (ISO 5349-1) High speed	1.31 ms ⁻²

Dimensions



(A) 3901.0 mm	(J) 3023.0 mm
(B) 1972.0 mm	(K) 828.0 mm
(C) 24.2°	(L) 42.0°
(D) 185.0 mm	(M) 97.0°
(E) 1082.0 mm	(N) 1727.0 mm
(F) 2657.0 mm	(O) 2024.0 mm
(G) 3378.0 mm	(P) 1374.0 mm
(H) 30.0°	(Q) 1643.0 mm
(I) 2177.0 mm	(Q*) 1520.0 mm

Attachments

Auger Accessories	Planer Accessories
Augers	Planers
Backhoes	Rear Stabilizers
Bale Forks	Root Grapples
Box Blades	Scarifiers
Breaker Accessories	Scrapers
Breakers	Seeders
Brushcat™ Rotary Cutters	Skeleton Buckets
Brush Saws	Snow Blades
Combination Buckets	Snow Pushers
Concrete Mixers	Snow V-Blades
Diggers	Sod Layers
Dozer Blades	Soil Conditioners
Drop Hammers	Spreaders
Dumping Hoppers	Steel Tracks
Flail Cutters	Stump Grinders
Graders	Sweepers
Grapples, Industrial	Tillers
Landplanes	Tilt-Tatch
Landscape Rakes	Tree Transplanters
Laser Equipment	Trench Compactors
Miscellaneous	Trenchers
Mixing Buckets	Utility Forks
Mowers	Utility Frames
Pallet Fork Accessories	Vibratory Rollers
Pallet Forks, Hydraulic	Wood Chippers